

Data sheet

Swelling tape adhesive

for bentonite swelling tapes.

[Show product](#)



Product video in further languages



article number:	010050
article group:	103 - Quellbandkleber+PU Quellpaste
GTIN:	4251689510311
customs tariff number:	32149000
packing unit:	ct
sales quantity unit:	1 Kt
weight per:	ct = 0.6 kg
material:	acrylate
colour:	black
density:	ca. 1,65 g/ml
consistency:	non-sagging paste, pasty
usage:	1 cartridge = approx. 7 metres
	ca. 40 - 50 ml/m
skin-over time: :	at 20°C
	approx. 8 hours
packaging :	310 ml cartridge
	20 cartridges per carton
adheres to:	concrete
subsurface:	clean, free of dust/grease and sound.
	The swelling tape adhesive will form a firm skin at normal temperatures (23°C, 50% R.H.).
minimum durability:	12 months after production
thermal scope of application:	+ 5 °C up to + 45 °C
storage:	Store in undamaged and unopened original packaging in a dry place out of direct sunlight.



MASTERTEC

SPEZIALARTIKEL FÜR DEN STAHLBETONBAU

disposal:

disposal must be in accordance with the pertinent national and local regulations. Hardened materials may be disposed of with regular household/commercial waste. Cartridges containing residual paste must be treated as hazardous waste.

Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Indication of law

The technical information reflects our current knowledge of Swelling tape adhesive. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Print date 07.05.2024 , last modified 24.03.2022