

# Data sheet

## MASTER-Connect joint sheet metal F150 mm

for joint sheet metal widths up to 150 mm



[Show product](#)



Product video in further languages



article number:	070196
article group:	210 - Connect (Blech + Band)
GTIN:	4251689513329
customs tariff number:	72123000
packing unit:	pc
sales quantity unit:	1 Stk
weight per:	pc = 2 kg
material:	steel plates: St 37, bright intermediate plates: specialty rubber screws: galvanised
colour:	grey, black
length of the plates:	250 mm or 330 mm
width of the plates:	100 mm
thickness steelplate / intermediate plate:	approx. 6 mm / 10 mm
weight:	2,00 kg
test certificate / approvals:	Investigation report UB 5.1/13-347 MFPA Leipzig
pressure water-tightness:	7 bar ( 70 m water column )
resistances (intermediate plate):	Oil and petrol Liquid manure and slurry Fermentation mash Diluted acids Alkalis Radon and methane gas
packaging:	1 piece per carton

scope of delivery:

2 pcs. steel plates, bright  
2 pcs. specialty rubber plates,  
6/8 pcs. NBR washers  
3/4 pcs. M 10 screws, galvanised  
3/4 pcs. M 10 nuts, galvanised

The product is delivered pre-assembled in a box

Substances according to the SVHC list contained or proportional weight $\geq 0.1\%$ :	No
Conform to REACH Guideline:	Yes
storage:	Store in undamaged and unopened original packaging in a dry place out of direct sunlight.
disposal:	Can be disposed of at municipal waste landfill sites, taking into account the local waste disposal regulations.

## Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

## Indication of law

The technical information reflects our current knowledge of MASTER-Connect joint sheet metal F150 mm. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

## The previous data sheets are no longer valid

Print date 17.05.2024 , last modified 24.03.2022