


Data sheet

ABS joint sheet metal cage 500-reinforced(V)-rough

for subsequent installation of joint sheet metal | height: 410 - 500 mm

Show product





Page 1 of 4



article group: 225 - ABS Dichtblechkorb (S+V) GTIN: 4251689501647 customs tariff number: 72119080 packing unit: pc sales quantity unit: 2.4 m material: bright steel colour: silvery suitable for: Optimized for joint sheet metal height 160 mm joint type: rough, according to DIN EN 1992-1-1 NA (EC2) allowable installation 410 - 500 mm height: storage: store in a dry place disposal: Can be disposed of at municipal waste landfill sites, taking into account the local waste disposal regulations	article number:	071212V
customs tariff number: 72119080 packing unit: pc sales quantity unit: 2.4 m material: bright steel colour: silvery suitable for: Optimized for joint sheet metal height 160 mm joint type: rough, according to DIN EN 1992-1-1 NA (EC2) allowable installation 410 - 500 mm height: storage: store in a dry place disposal: Can be disposed of at municipal waste landfill sites, taking into account the	article group:	225 - ABS Dichtblechkorb (S+V)
packing unit: sales quantity unit: material: bright steel colour: silvery suitable for: Optimized for joint sheet metal height 160 mm joint type: rough, according to DIN EN 1992-1-1 NA (EC2) allowable installation height: storage: store in a dry place disposal: Can be disposed of at municipal waste landfill sites, taking into account the	GTIN:	4251689501647
sales quantity unit: 2.4 m material: bright steel colour: silvery suitable for: Optimized for joint sheet metal height 160 mm joint type: rough, according to DIN EN 1992-1-1 NA (EC2) allowable installation height: storage: store in a dry place disposal: Can be disposed of at municipal waste landfill sites, taking into account the	customs tariff number:	72119080
material: bright steel colour: silvery suitable for: Optimized for joint sheet metal height 160 mm joint type: rough, according to DIN EN 1992-1-1 NA (EC2) allowable installation 410 - 500 mm height: storage: store in a dry place disposal: Can be disposed of at municipal waste landfill sites, taking into account the	packing unit:	рс
colour: silvery suitable for: Optimized for joint sheet metal height 160 mm joint type: rough, according to DIN EN 1992-1-1 NA (EC2) allowable installation 410 - 500 mm height: storage: store in a dry place disposal: Can be disposed of at municipal waste landfill sites, taking into account the	sales quantity unit:	2.4 m
suitable for: joint type: rough, according to DIN EN 1992-1-1 NA (EC2) allowable installation height: storage: storage: store in a dry place disposal: Can be disposed of at municipal waste landfill sites, taking into account the	material:	bright steel
joint type: rough, according to DIN EN 1992-1-1 NA (EC2) allowable installation 410 - 500 mm height: storage: store in a dry place disposal: Can be disposed of at municipal waste landfill sites, taking into account the	colour:	silvery
allowable installation height: storage: store in a dry place disposal: Can be disposed of at municipal waste landfill sites, taking into account the	suitable for:	Optimized for joint sheet metal height 160 mm
height: storage: store in a dry place disposal: Can be disposed of at municipal waste landfill sites, taking into account the	joint type:	rough, according to DIN EN 1992-1-1 NA (EC2)
storage: store in a dry place disposal: Can be disposed of at municipal waste landfill sites, taking into account the	allowable installation	410 - 500 mm
disposal: Can be disposed of at municipal waste landfill sites, taking into account the	height:	
landfill sites, taking into account the	storage:	store in a dry place
	disposal:	Can be disposed of at municipal waste
local waste disposal regulations		landfill sites, taking into account the
		local waste disposal regulations



Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Lifetime

The useful life of buildings is designed for 50 years, and so are the products that are installed. However, this can be shortened by external influences. The expected lifetime of our products depends to a large extent on the installation location (e.g. buried installation, damp environment, offshore, etc.). In addition, there are external influences such as exposure to chemical influences (e.g. acids, aggressive media, aqueous solutions, industrial waste water, oils, etc.) and ambient temperatures / operating temperatures. Ultimately, no generally valid statement can be made about the guaranteed service life of our MASTERTEC products, as this depends on many parameters (use, environmental influences, installation requirements, safety regulations, etc.). To ensure safe operation, we recommend continuous testing of the product, as part of an operating and maintenance manual to be prepared by the customer in accordance with the safety requirements.

Indication of law

The technical information reflects our current knowledge of the product ABS joint sheet metal cage 500-reinforced(V)-rough. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to

Kommanditgesellschaft:

HRA 9888, Sitz Oberhaid

Vertriebs-Verwaltungs GmbH,



necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Print date 22.07.2024, last modified 05.09.2023