

# Data sheet

# Master-Home-Connect (MHC) - single-utility - 10 mtr

single-compartment house lead-in for media lines from 4 to 40 mm - with 10.0 mtr cable conduit outer Ø 75 mm







Show product



Seite 1 von 4



article number:	080037
article group:	410 - MHC + Zubehör
GTIN:	4251689507120
customs tariff number:	39259080
packing unit:	Set
sales quantity unit:	1 Set
test certificate / approvals:	- DVGW VP 601 (Chapter 4.5) "Gas and water tightness of
:	the installed house entry)
	- Individual components additionally tested for water
	pressure tightness
scope of delivery:	- 0.6 m lining pipe (with closure plug) incl. sealing collar,
	connector and installation scale
	- MHC gasket insert Solo
	- ground spike Ø 20 mm
	- Double threaded clamp with connection clamp
	- 1 set each of MHC spacer solo and duo
	- closure plugs for cable conduit-solo with multi-insert
	- 10.0 mtr cable conduit Ø 75 mm



#### **Basis**

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

### Lifetime

The useful life of buildings is designed for 50 years, and so are the products that are installed. However, this can be shortened by external influences. The expected lifetime of our products depends to a large extent on the installation location (e.g. buried installation, damp environment, offshore, etc.). In addition, there are external influences such as exposure to chemical influences (e.g. acids, aggressive media, aqueous solutions, industrial waste water, oils, etc.) and ambient temperatures / operating temperatures. Ultimately, no generally valid statement can be made about the guaranteed service life of our MASTERTEC products, as this depends on many parameters (use, environmental influences, installation requirements, safety regulations, etc.). To ensure safe operation, we recommend continuous testing of the product, as part of an operating and maintenance manual to be prepared by the customer in accordance with the safety requirements.

#### **Indication of law**

The technical information reflects our current knowledge ofMaster-Home-Connect (MHC) - single-utility – 10 mtr. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product

Seite 3 von 4

EORI-Nr.: DE 4774124



specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

## The previous data sheets are no longer valid

Print date 30.06.2024, last modified 24.03.2022