

Data sheet

Construction joint tape, internal, A 19

Tape width 190 mm Roll length 25 m

Show product







article number:	080500
article group:	211 - PVC Fugenband und Dichtungsrohr
GTIN:	4251689513411
customs tariff number:	39162000
packing unit:	Roll
sales quantity unit:	25 m
weight per:	Roll = 24 kg
material:	PVC-P
	NB (not compatible with bitumen)
colour:	black
Roll length:	25 m
Tape width (a):	190 mm
Expansion part width (b):	70 mm
Expansion part thickness	3 mm
(c):	
Outside thickness (d):	2.5 mm
Shore-hardness A:	72 ± 5°, acc. to DIN 53505
Elongation at break:	min. ≥ 275%, acc. to
	DIN EN ISO 527-2
Tensile strength:	min. $\geq 10 \text{ N/mm}^2$,
	DIN EN ISO 527-2
Safety aspect:	The Joint tape, factory standard PVC does not contain any
	hazardous substances and poses
	no problems whatsoever in terms of handling and
	application. To the best of our knowledge, it
	contains no substances that are harmful to groundwater or
	could trigger health problems or
	allergic reactions in the installer.
	Nonetheless, we recommend that an appropriate level of
	hygiene is observed during application
	and that hands are washed as a basic rule before meals.



Substances according to	No
the SVHC list contained or	
proportional weight ≥0.1%:	
Conform to REACH	Yes
Guideline:	
storage:	Store in undamaged and unopened
	original packaging in a dry place out of direct sunlight.
disposal:	Can be disposed of at municipal waste landfill sites, taking
	into account the
	local waste disposal regulations.



Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Lifetime

The useful life of buildings is designed for 50 years, and so are the products that are installed. However, this can be shortened by external influences. The expected lifetime of our products depends to a large extent on the installation location (e.g. buried installation, damp environment, offshore, etc.). In addition, there are external influences such as exposure to chemical influences (e.g. acids, aggressive media, aqueous solutions, industrial waste water, oils, etc.) and ambient temperatures / operating temperatures. Ultimately, no generally valid statement can be made about the guaranteed service life of our MASTERTEC products, as this depends on many parameters (use, environmental influences, installation requirements, safety regulations, etc.). To ensure safe operation, we recommend continuous testing of the product, as part of an operating and maintenance manual to be prepared by the customer in accordance with the safety requirements.

Indication of law

The technical information reflects our current knowledge of the product Construction joint tape, internal, A 19. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product

EORI-Nr.: DE 4774124

Kommanditgesellschaft:



specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Print date 24.08.2024, last modified 24.03.2022