

Data sheet

Crack inducer tube Q1 (Ø 88 mm) - 3.00 m

diameter 88 mm length 3000 mm







Seite 1 von 3



article group: 211 - PVC Fugenband und Dichtungsrohr GTIN: 4251689513602 customs tariff number: 39259080 packing unit: pc sales quantity unit: 3 m weight per: pc = 11 kg material: PVC-P casing PVC-U pipe core colour: black length: 3,0 m diameter: 88 mm wall thickness: 240 - 350 mm Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Yes Guideline: storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the local waste disposal regulations.	article number:	080712
customs tariff number: packing unit: pc sales quantity unit: yc = 11 kg material: PVC-P casing PVC-U pipe core colour: black length: 3,0 m diameter: 88 mm wall thickness: 240 - 350 mm Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Guideline: storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	article group:	211 - PVC Fugenband und Dichtungsrohr
packing unit: sales quantity unit: weight per: pc = 11 kg material: PVC-U pipe core colour: black length: 3,0 m diameter: 88 mm wall thickness: 240 - 350 mm Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Guideline: storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	GTIN:	4251689513602
sales quantity unit: weight per: pc = 11 kg PVC-P casing PVC-U pipe core colour: black length: 3,0 m diameter: 88 mm wall thickness: 240 - 350 mm Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Guideline: storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	customs tariff number:	39259080
weight per: pc = 11 kg material: PVC-P casing PVC-U pipe core colour: black length: 3,0 m diameter: 88 mm wall thickness: 240 - 350 mm Substances according to the SVHC list contained or proportional weight ≥0.1%: No conform to REACH Yes Guideline: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	packing unit:	рс
material: PVC-U pipe core colour: black length: 3,0 m diameter: 88 mm wall thickness: 240 - 350 mm Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Guideline: storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	sales quantity unit:	3 m
PVC-U pipe core colour: black length: 3,0 m diameter: 88 mm wall thickness: 240 - 350 mm Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Yes Guideline: storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	weight per:	pc = 11 kg
colour: length: 3,0 m diameter: 88 mm wall thickness: 240 - 350 mm Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Guideline: storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	material:	PVC-P casing
length: 3,0 m diameter: 88 mm wall thickness: 240 - 350 mm Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Yes Guideline: storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the		PVC-U pipe core
diameter: 88 mm wall thickness: 240 - 350 mm Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Yes Guideline: storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	colour:	black
wall thickness: 240 - 350 mm Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Yes Guideline: storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	length:	3,0 m
Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Guideline: storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	diameter:	88 mm
the SVHC list contained or proportional weight ≥0.1%: conform to REACH Yes Guideline: storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	wall thickness:	240 - 350 mm
proportional weight ≥0.1%: conform to REACH Guideline: storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	Substances according to	No
conform to REACH Guideline: storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	the SVHC list contained or	
Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	proportional weight ≥0.1%:	
storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	conform to REACH	Yes
original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	Guideline:	
disposal: Can be disposed of at municipal waste landfill sites, taking into account the	storage:	Store in undamaged and unopened
landfill sites, taking into account the		original packaging in a dry place out of direct sunlight.
	disposal:	Can be disposed of at municipal waste
local waste disposal regulations.		landfill sites, taking into account the
		local waste disposal regulations.



Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Indication of law

The technical information reflects our current knowledge of Crack inducer tube Q1 (Ø 88 mm) - 3.00 m. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Print date 19.05.2024, last modified 03.03.2023

Seite 3 von 3