

Data sheet

KG 2000 ground drain Ø200/500 mm-Base with plug

type ground drain (BDL) - colour: green

Show product



Seite 1 von 4





Seite 2 von 4



article group: 418 - BDL GTIN: 4251689507854 customs tariff number: 39172290 packing unit: pc sales quantity unit: 1 Stk material: pipe: PVC-U colour: pipe: green thermal scope of approx10° C up to +60° C application: waterpressuretightness: 7 bar (70 m water column) storage: Store in a dry place and out of direct sunlight disposal: Can be disposed of at municipal waste landfill sites, taking into account the local waste disposal regulations.	article number:	080989D
customs tariff number: packing unit: pc sales quantity unit: 1 Stk material: pipe: PVC-U colour: pipe: green thermal scope of approx10° C up to +60° C application: waterpressuretightness: 7 bar (70 m water column) storage: Store in a dry place and out of direct sunlight disposal: Can be disposed of at municipal waste landfill sites,	article group:	418 - BDL
packing unit: sales quantity unit: 1 Stk material: pipe: PVC-U colour: pipe: green thermal scope of approx10° C up to +60° C application: waterpressuretightness: 7 bar (70 m water column) storage: Store in a dry place and out of direct sunlight disposal: Can be disposed of at municipal waste landfill sites,	GTIN:	4251689507854
sales quantity unit: 1 Stk material: pipe: PVC-U colour: pipe: green thermal scope of approx10° C up to +60° C application: waterpressuretightness: 7 bar (70 m water column) storage: Store in a dry place and out of direct sunlight disposal: Can be disposed of at municipal waste landfill sites,	customs tariff number:	39172290
material: pipe: PVC-U colour: pipe: green thermal scope of approx10° C up to +60° C application: waterpressuretightness: 7 bar (70 m water column) storage: Store in a dry place and out of direct sunlight disposal: Can be disposed of at municipal waste landfill sites,	packing unit:	рс
colour: pipe: green thermal scope of approx10° C up to +60° C application: waterpressuretightness: 7 bar (70 m water column) storage: Store in a dry place and out of direct sunlight disposal: Can be disposed of at municipal waste landfill sites,	sales quantity unit:	1 Stk
thermal scope of approx10° C up to +60° C application: waterpressuretightness: 7 bar (70 m water column) storage: Store in a dry place and out of direct sunlight disposal: Can be disposed of at municipal waste landfill sites,	material:	pipe: PVC-U
application: waterpressuretightness: 7 bar (70 m water column) storage: Store in a dry place and out of direct sunlight disposal: Can be disposed of at municipal waste landfill sites,	colour:	pipe: green
waterpressuretightness: 7 bar (70 m water column) storage: Store in a dry place and out of direct sunlight disposal: Can be disposed of at municipal waste landfill sites,	thermal scope of	approx10° C up to +60° C
storage: Store in a dry place and out of direct sunlight disposal: Can be disposed of at municipal waste landfill sites,	application:	
disposal: Can be disposed of at municipal waste landfill sites,	waterpressuretightness:	7 bar (70 m water column)
	storage:	Store in a dry place and out of direct sunlight
taking into account the local waste disposal regulations.	disposal:	Can be disposed of at municipal waste landfill sites,
		taking into account the local waste disposal regulations.



Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Indication of law

The technical information reflects our current knowledge of KG 2000 ground drain Ø200/500 mm-Base with plug. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Print date 20.05.2024

EORI-Nr.: DE 4774124